

## 15 LB. SST DREDGE



Easily sample most types of bottom surfaces. Constructed from stainless steel and powder-coated carbon steel for corrosion resistance.

15 lb. SST Dredge  
Part #445.10

## 25 LB. SST DREDGE



Easily sample most types of bottom surfaces. The top of the sampling chamber is screened to allow water flow during deployment and reduce the frontal shock wave that may displace sediment as the dredge contacts the sample surface.

25 lb. SST Dredge  
Part #445.60



## EKMAN DREDGE

This is used for sampling benthic communities inhabiting soft bottomed aquatic environments.

Ekman Dredge  
Part #445.11



## SST BAILER

Collect composite samples from 2" wells and boreholes. Feature a tubular stainless steel body with a wire loop bail and fluopolymer check ball on all models except model #2100.36 which is a top fill model.

1 3/4" x 3' Tapered SST Bailer  
(Bottom Fill)  
Part #451.00 | Unit Price:

1 3/4" x 3' Tapered SST Bailer  
(Top Fill)  
Part #2100.39



## EZ KLEEN SOIL PROBE

AMS EZ Kleen Soil Probes have been designed to facilitate easy soil core extraction. Unlike standard slotted soil probes; the easy clean has a specialized heat treated tip designed to reduce friction as the soil enters the probe body.

7/8" X 33" EZ Kleen Soil Probe  
Part #401.36

1-1/8" X 33" EZ Kleen Soil Probe  
Part #401.37



## 1 1/4" X 24" REPLACEABLE TIP SAND PROBE

The NEW AMS Stainless Steel Replaceable Tip Sand/Loose Sediment Soil Probe is ideal for obtaining unconsolidated soil samples in a 1" x 24" poly liner.

1 1/4" x 24" Replaceable Tip Sand Probe  
Part #424.37

1 1/4" x 36" Replaceable Tip Sand Probe  
Part #424.39