

BESANTEK CCTV Tester is used for displaying video, controlling PTZ, generating images, capturing data of RS485 and testing LAN cables etc. It is easy to operate and simple for the technician to install and maintain CCTV system.

Features:

- 3.5" LCD screen 320 x 240 high resolution.
- The brightness, contrast, color saturation is adjustable for TFT LCD screen.
- LCD screen displays the testing result visually, short, broken, cross, etc.
- CVBS & analog signal testing.
- Audio signal testing.
- Check cable wiremap for RJ45 and BNC cable.
- PTZ control and audio testing.
- Color bar generating, captures and analyzes RS485 controlling data.
- Video generate and display, automatically adapts and displays the video format of NTSC/PAL.
- Supply power for cameras.
- Built-in 3000mA lithium battery.
- Data analysis to test the attenuation amplitude of video signal.
- DC 12V power output for cameras, the max. current output is 1A.
- RS485 control interface, support baud rates with 2400/4800/9600.
- Multi-protocols. Support more than 20 kinds PTZ protocol, such as Pelco-D, Pelco-P, Samsung, Minking, etc.
- Accessories: Instruction manual, DC 5V 1A charging adaptor, BNC cable, audio cable, RS485 data cable, camera power cable, pendant rope, remote and carry bag.



BST-LAN12

Technical Specification:

BST-LAN12

Audio Signal Input	Microphone or other audio devices
Color Bar	White, blue, purple, green, yellow, black, red
Baud Rates	2400/4800/9600
Video Format	NTSC/PAL
Video Output	CVBS/Analog signal
Operating Temperature & Humidity	-10°C~50°C, 30%~60%RH
Auto-off Time	15min/30min/1h/2h
Working Time	Independent working time can be up to 12 hours
Power Source	DC5V/1A, built-in 3.7V Li-battery, detachable
Dimensions	Indicator: 206 x 112 x 49 mm Remote: 107 x 30 x 24 mm
Weight	Indicator: Approx. 512g Remote: Approx. 36g

Accessories



Ordering Information:

- BST-LAN12: CCTV Tester.