

3671 pH/ORP controller

Monitor and control process water using pH and ORP sensors



- Automatic pH temperature compensation 0-100°C.
- Set points on front panel
- Large bright red LED screen
- Easy to install

Description

Global Water's pH/ORP Controller is a 1/8 DIN panel temperature.

The pH/ORP controller uses an all solid design to achieve low power consumption and reduced internal heating. Each controller is heat cycled 100 hours before shipment. The controller offers automatic pH temperature compensation from 0 to 100°C and set points that cover the entire sensor span.

mount controller with dual SPDT Hi/Lo relays, manual set points and calibration potentiometers set into the front of the panel. The pH/OPR controller features a voltage/recorder output and an internal pH/ORP select switch. The display is a large 0.56" high efficiency bright red LED. Sensor connectors are a BNC input and spade lug screw type connector block. The pH/ORP Controller requires a Pt-100 ATC probe or a simulation resistor for

Specifications

mV (± digit): ±0.1 %

Range: pH: 0 to 14.0 Temp: 0 to 100 °C mV:-1990 to +1990 Resolution: *pH:* 0.1 Temp: 1 °C *mV:* 10 Accuracy: pH (± digit): 0.1 (relative) when standardized within 2 pH Temp (± digit): 1

Input Impedance: >1012 ohms Temperature Compensation: Auto 0.0 to 100.0 °C Recorder Output (Full Range). *pH:* 1400 mV Temp: 1000 mV mV: ± 1990mV

Dual point ON/OFF control: pH or ORP with internal select switch Dead Band: ± 0.1 pH for each set point Relay Output: 8 Amp at 115 VAC, 4 Amp at 230 VAC Readout: 0 .56" high efficiency red LED display Power Source: 115 VAC, 230 VAC ± 15% 50/60 Hz Dimension: 3.75x2x6.75(96x48x172mm) Weight: 1.5 lbs (0.69 kg)

Options and Accessories

3671 KB pH/ORP Controller Includes controller, pH/Ref Electrode, and ATC probe

600P pH/Ref Electrode


Industrial pH sensor: epoxy with BNC connector. Comes with a 3' cable. Max Temp. 60° C

600E-ORP ORP Transmitter Sensor Industrial ORP sensor: epoxy with BNC connector, Max Temp. 60° C, 3-ft cable.

Global Water for all your instrumentation needs: Water Level Water Flow Water Samplers Water Quality Weather Remote Monitoring

Contact

Control





In the U.S. call toll free at 1-800-876-1172 International: 916-638-3429 Fax: 916-638-3270 Email: globalw@globalw.com Visit our online catalog at: www.globalw.com Our Address: 11390 Amalgam Way Gold River, CA 95670