

RM6-N

Space saving, compact and versatile 6 decade resistance box with wide range

The RM6-N is a space saving 6 decade resistance box, 3 models are available covering the range 1Ω to $111,111M\Omega$. An additional $1k\Omega$ resistor is available at the terminals enabling the user to make a simple divider. The RM6-N incorporates 0.4 watt resistors with a specified accuracy of $\pm 1\%$.

Designed for durability and ease of maintenance, the case is high impact polystyrene and the size is only 190 x 140 x 70mm. The RM6-N's constitute an ideal tool for use in all electrical and electronic laboratories or workshop environments offering a wide range of values with minimum cost.

Technical Specifications

Decade	Accuracy	Maximum Current	RM6-N	RM6-N2	RM6-N3
10 x 1Ω	±1%	600mA		1	
10 x 10Ω	±1%	200mA	1	1	
$10 \times 100\Omega$	±1%	60mA	1	1	✓
10 x 1kΩ	±1%	20mA	1	1	✓
10×10 k Ω	±1%	6mA	1	1	\checkmark
$10 \times 100 \text{k}\Omega$	±1%	2mA	/	✓	\checkmark
$10 \times 1M\Omega$	±1%	0.6mA	1		\checkmark
$10 \times 10 M\Omega$	±1%	0.2mA			1

Maximum Continuous Working Voltage

70VDC, 33Vrms

Resistors

Metal film 0.4W at 70°C Temperature coefficient ± 100 ppm/°C Except 1 Ω : ± 200 ppm/°C

Switches

Silver plated brass contact resistance = $10m\Omega$, positive click mechanism. Insulation resistance >50,000M Ω

Residual Resistance

 $< 0.1\Omega$

X1MΩ X100kΩ X10kΩ X10kΩ

Key Features

- 6 decades
- Range 10Ω to $10M\Omega$
- Accuracy 1%
- Low cost

Ideal For

- Engineering departments
- Laboratories/workshops
- Calibration houses

General Specifications

Dimensions

190 x 140 x 70mm / 7.5 x 5.5 x 2.8" (w x h x d) approx

Mass

0.49kg / 1lbs

Case

High impact polystyrene

Services

1 year warranty (subject to product registration with Seaward. Visit

www.seaward.co.uk/register-product)

Service and calibration by Calibrationhouse.

Go to **www.calibrationhouse.com** for more information.

Part Numbers

RM6-N	930154
RM6-N2	930155
RM6-N3	930156

Email: sales@seaward.co.uk